



MULTISTRADA 1260 ENDURO

Engine	
Type	Ducati Testastretta DVT with Desmodromic Variable Timing, L-Twin cylinder, 4 valves per cylinder, Dual Spark, liquid cooled
Displacement	1,262 cc
Bore X stroke	106 x 71.5 mm
Compression ratio	13:1
Power	116.4 kW (158,3 hp) @ 9,500 rpm
Torque	128 Nm (94,4 lb-ft) @ 7,500 rpm
Fuel injection	Bosch electronic fuel injection system, elliptical throttle bodies with Ride-by-Wire, equivalent diameter 56 mm
Exhaust	Stainless steel muffler with catalytic converter and 2 lambda probes, aluminium tail pipes
Transmission	
Gearbox	6 speed with Ducati Quick Shift (DQS) up/down
Primary drive	Straight cut gears; Ratio 1.84:1
Ratio	1=38/14 2=30/17 3=27/20 4=24/22 5=23/24 6=22/25
Final drive	Chain; Front sprocket 15; Rear sprocket 43
Clutch	Light action, wet, multiplate clutch with hydraulic control. Self-servo action on drive, slipper action on over-run
Chassis	
Frame	Tubular steel Trellis frame
Front suspension	Sachs 48 mm fully adjustable usd forks. Electronic compression and rebound damping adjustment with Ducati Skyhook Suspension (DSS) Evo
Front wheel	Tubeless spoked wheel in light alloy 3" x 19"
Front tyre	Pirelli Scorpion Trail II 120/70 R19 as optional Pirelli Scorpion Rally same measure
Rear Suspension	Fully adjustable Sachs unit. Electronic compression and rebound damping adjustment. Electronic spring pre-load adjustment with Ducati Skyhook Suspension (DSS) Evo. Aluminium single-sided swingarm
Rear Wheel	Tubeless spoked wheel in light alloy 4.50" x 17"
Rear tyre	Pirelli Scorpion Trail II 170/60 R17 as optional Pirelli Scorpion Rally same measure
Wheel travel (front/rear)	185 mm - 185 mm (7.3 in - 7.3 in)
Front brake	2 x 320 mm semi-floating discs, radially mounted Brembo monobloc M4.32-piston callipers, 2-pad, radial pump with Bosch Cornering ABS as standard equipment
Rear brake	265 mm disc, 2-piston floating calliper, with Bosch Cornering ABS as standard equipment
Instrumentation	Color TFT display 5"
Dimensions and weights	
Dry weight	225 kg (496 lb)
Kerb weight	254 kg (560 lb)
Seat height	Not adjustable 860 mm (880 with high seat - 840 mm with low seat)
Wheelbase	1,592 mm
Rake	25°
Trail	112 mm
Fuel tank capacity	30 l
Number of seats	Dual seat
Equipment	
Safety equipment	Vehicle Hold Control (VHC), Riding Modes, Power Modes, Ducati Safety Pack (Bosch Cornering ABS + DTC), Ducati Wheelie Control (DWC), Ducati Cornering Lights
Standard equipment	Ducati Skyhook Suspension (DSS) Evo, Ducati Quick Shift (DQS) up/down, Cruise control, Hands-Free, Backlit handlebar switches, Ducati Multimedia System (DMS), Full-colour TFT display, Full LED headlamp, Auto-off indicators
Additional equipment	
Ready for	Anti-theft
Warranty	
Warranty	24 months, unlimited mileage
Maintenance service intervals	15,000 km (9,000 miles) / 12 months
Valve clearance check	30,000 km (18,000 miles)
Emissions and consumption	
Standard	Euro 4
CO ₂ Emissions	130 g/km
Consumption	5.5l/100 km

*Kerb weights indicate total bike weight with all operating consumable liquids and a fuel tank filled to 90% of capacity (as per EC standard 93/93).